

DAI-EL PACKING

Fluoroelastomers



50A



40A



25A

Feature

1. Enable to use against the wide range of liquid.
Not only acid but also alkali.
2. Elastic rubber fitted the flange in prevents leakage.
3. Unique design

The list of corrosion resistance

Liquid	corrosion resistance
Hydrochloric acid 35 %	○
Hydrofluoric aci 50 %	○
Sulfuric acid 98 %	○
Phosphoric acid 85 %	○

Usage



World Chemical Magnet Pumps
The best for GVF, GSF and GR



YD-GVF



YD-GSF



YD-GR

 World Chemical Co., Ltd.

Main Office

7F., TOUSEN Bldg., 1-5-2, Higashi-Azabu, Minato-ku, Tokyo,
106-0044 Japan

Chemical Pump Division ☎ 03(3588)1140 FAX 03(3588)1141

Overseas Sales Division ☎ 03(3588)1866 FAX 03(3588)1141

E-mail overseas@wcc.co.jp

Nagoya Office ☎ 052(701)1227 FAX 052(701)1250

Osaka Office ☎ 06(6584)3185 FAX 06(6584)3160

Fukuoka Office ☎ 0942(51)8533 FAX 0942(51)8534

■ Distributed by;

<http://www.wcc.co.jp>